

<u>Home</u>

Products ~

Help & Support

Industries oducts / Fittings and Quick Couplings / Pneumatic Function Fittings and Flow Control / Piloted Fittings / Pneumatic Blocking Fittings / 7881 13 13

Prieumatic Blocking Fittings Finc Part #: 7881 13 13 S. 🛛 Sa Divi Parl Low Parc 1 ru CS 4 350 \oplus Frar Blocking fittings, mounted in pairs on a cylinder, lock the piston by simultaneously cutting off the supply and exhaust

View Series Page 😑 Share / Email 📌 Print 🖶

when the pilot signal is removed.

Technical Specifications

Connection 2 Thread Size: Maximum Operating	G1/4	Maximum Operating Pressure: Minimum Operating Temperature:	10 bar	
Temperature: Connection 1 Thread Size:	70 °C G1/4		-20 °C	
Connection 2 Type:	Female BSPP	Quantity per Box:	1	
Pilot Port Type:	Metric Thread : M5	Weight:	0.12 kg	
Body Material: Connection 2 Tube Outside Diameter: Gripping Ring Material:	NICKEL PLATED BRASS	Industry Application: Pneumatics, Automotive Process Media: Compressed air Specifications Met: ROHS, PED, REACH Product Type: Blocking Fittings	Robotics, Machine Tools, Textile, Packaging, Pneumatics, Automotive Process	
	na			
	na			
O-Ring Material:	NBR		5 5	
Thread Sealant Material:	na	Connection 1 Type:	Male BSPP	
		Shape:	Blocking fitting female	
California Residents: Prop-65 Warning				

▲ Safety Warning

Item Information	+
CAD Drawings + Files	+
Related Documents	+
	9

Related Products



<u>Home</u>

Products ~

Help & Support

Industries

Modular & Multi-port <u>WherePhotButy</u>ic Push-in Connectors - LF

3000®

Accessories for Push-In Fittings - I F 3000®

Pneumatic Flow Control Regulators in Polymer or Nickel-Plated Brass

Tubing

Fluoropolymer (PFA)

Polyethyl

Tubi



Americas

USA, Canada, Mexico

cparker@support.parker.com <u>1-800-272-7537</u>

Europe

00800 27 27 5374

AOG (Aircraft on Ground)

<u>1-949-851-4357</u>

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :

© PARKER HANNIFIN CORP 2025

ENGINEERING YOUR SUCCESS.

SITE MAP SAFETY PRIVACY POLICIES TERMS AND CONDITIONS

7881 13 13 - Pneumatic Blocking Fittings | Parker NA

Polyamide (PA)

Flexible Tubing

e



<u>Home</u>

Products v

Help & Support

Industries

Where To Buy

Ø