Product datasheet Characteristics

A9A26976

terminal shield - 2 poles - 36 mm - for iC60, iID, Reflex iC60, iSW-NA



Main

Product name	IKQ
Product or component type	Terminal shield
Accessory / separate part category	Insulation accessory
Colour	White

Complementary

Range compatibility	Acti 9 iKQ	
Poles description	2P	
Mounting mode	By clips	
[Ui] rated insulation voltage	500 V	
Connection pitch	36 mm	
Compatibility code	Reflex_iC60	
Compatibility code	Retiex_IC6U	

Packing Units

Package 1 Weight	0.046 kg	
Package 1 Height	0.400 dm	
Package 1 width	0.800 dm	
Package 1 Length	1.050 dm	

Offer Sustainability

Accessory / separate part category Colour White Complementary Range compatibility Acti 9 iKQ Poles description 2P Mounting mode By clips [Ui] rated insulation voltage 500 V Connection pitch 36 mm Compatibility code Reflex_iC60 Packing Units Package 1 Weight 0.400 dm Package 1 Height 0.800 dm Package 1 Length 1.050 dm Offer Sustainability REACh Regulation REACh Regulation REACh Declaration REACh Gree of SVHC Yes EU ROHS Directive Compliant EU ROHS Declaration Toxic heavy metal free Yes Mercury free Yes RoHS exemption information Yes	Product name	IKQ	
Colour White Complementary Range compatibility Acti 9 iKQ Poles description 2P Mounting mode By clips [Ui] rated insulation voltage 500 V Connection pitch 36 mm Compatibility code Reflex_iC60 Packing Units Package 1 Weight 0.046 kg Package 1 Height 0.400 dm Package 1 Length 0.800 dm Package 1 Length 1.050 dm Offer Sustainability REACh Regulation REACh Regulation REACh Declaration REACh Fire of SVHC Yes EU RoHS Directive Compliant EU RoHS Declaration Toxic heavy metal free Yes RoHS exemption information Yes China RoHS Regulation China RoHS declaration	Product or component type	Terminal shield	
Complementary Range compatibility Acti 9 iKQ Poles description 2P Mounting mode By clips [Ui] rated insulation voltage 500 V Connection pitch 36 mm Compatibility code Reflex_iC60 Packing Units Package 1 Weight 0.400 dm Package 1 Height 0.400 dm Package 1 Height 1.050 dm Offer Sustainability REACh Declaration REACh Declaration REACh Declaration Toxic heavy metal free Yes Mercury free Wes RoHS exemption information Yes China RoHS Regulation China RoHS declaration	Accessory / separate part category	Insulation accessory	
Poles description 2P Mounting mode By clips [Ui] rated insulation voltage 500 V Connection pitch 36 mm Compatibility code Reflex_iC60 Packing Units Package 1 Weight 0.400 dm Package 1 Height 0.400 dm Package 1 Length 1.050 dm Offer Sustainability REACh Regulation REACh Declaration REACh free of SVHC Yes EU ROHS Directive Compliant EU ROHS Declaration Toxic heavy metal free Yes Mercury free Yes RoHS exemption information Yes China RoHS Regulation Connection of the connection of	Colour	White	
Range compatibility Acti 9 iKQ Poles description 2P Mounting mode By clips [Ui] rated insulation voltage 500 V Connection pitch 36 mm Compatibility code Reflex_iC60 Packing Units Package 1 Weight 0.046 kg Package 1 Height 0.400 dm Package 1 width 0.800 dm Package 1 Length 1.050 dm Offer Sustainability REACh Regulation REACh Regulation REACh free of SVHC Yes EU ROHS Directive Compliant EU ROHS Declaration Toxic heavy metal free Yes RoHS exemption information Yes China RoHS Regulation	Complementary		
Mounting mode By clips [Ui] rated insulation voltage 500 V Connection pitch 36 mm Compatibility code Reflex_iC60 Packing Units Package 1 Weight 0.046 kg Package 1 Height 0.400 dm Package 1 width 0.800 dm Package 1 Length 1.050 dm Offer Sustainability REACh Regulation REACh Declaration REACh free of SVHC Yes EU RoHS Directive Compliant EU RoHS Declaration Toxic heavy metal free Yes Mercury free Yes RoHS exemption information Yes China RoHS Regulation China RoHS declaration	-	Acti 9 iKQ	
[Ui] rated insulation voltage 500 V Connection pitch 36 mm Compatibility code Reflex_iC60 Packing Units Package 1 Weight 0.400 dm Package 1 Height 0.800 dm Package 1 Length 1.050 dm Offer Sustainability REACh Regulation REACh Declaration REACh free of SVHC Yes EU ROHS Directive Compliant EU ROHS Declaration Toxic heavy metal free Yes RoHS exemption information Yes China RoHS Regulation Composition China RoHS declaration Yes China RoHS Regulation Yes China RoHS Regulation Composition Composition China RoHS declaration Connection Package 1 Ammunication April 1 Ammunication Package 1 Ammunication Pa	Poles description	2P	
Connection pitch 36 mm Compatibility code Reflex_iC60 Packing Units Package 1 Weight 0.046 kg Package 1 Height 0.400 dm Package 1 width 0.800 dm Package 1 Length 1.050 dm Offer Sustainability REACh Regulation REACh Declaration REACh free of SVHC Yes EU RoHS Directive Compliant EU RoHS Declaration Toxic heavy metal free Yes Mercury free Yes RoHS exemption information Yes China RoHS Regulation China RoHS declaration China RoHS Regulation Yes China RoHS Regulation Yes	Mounting mode	By clips	
Compatibility code Reflex_iC60 Packing Units Package 1 Weight 0.046 kg Package 1 Height 0.400 dm Package 1 width 0.800 dm Package 1 Length 1.050 dm Offer Sustainability REACh Regulation REACh Peclaration REACh free of SVHC Yes EU RoHS Directive Compliant EU RoHS Declaration Toxic heavy metal free Yes Mercury free Yes RoHS exemption information Yes China RoHS Regulation China RoHS Regulation China RoHS Regulation	[Ui] rated insulation voltage	500 V	
Packing Units Package 1 Weight 0.046 kg Package 1 Height 0.400 dm Package 1 width 0.800 dm Package 1 Length 1.050 dm Offer Sustainability REACh Regulation REACh Declaration REACh free of SVHC Yes EU RoHS Directive Compliant EU RoHS Declaration Toxic heavy metal free Yes Mercury free Yes ROHS exemption information Yes China RoHS Regulation China RoHS declaration China RoHS Regulation China RoHS declaration	Connection pitch	36 mm	
Package 1 Height 0.400 dm Package 1 width 0.800 dm Package 1 Length 1.050 dm Offer Sustainability REACh Regulation REACh Declaration REACh free of SVHC Yes EU RoHS Directive Compliant EU RoHS Declaration Toxic heavy metal free Yes Mercury free Yes RoHS exemption information Yes China RoHS Regulation China RoHS declaration	Compatibility code	Reflex_iC60	
Package 1 width 0.800 dm Package 1 Length 1.050 dm Offer Sustainability REACh Regulation REACh Declaration REACh free of SVHC Yes EU RoHS Directive Compliant EU RoHS Declaration Toxic heavy metal free Yes Mercury free Yes RoHS exemption information Yes China RoHS Regulation China RoHS declaration		0.046 kg	
Package 1 Length 1.050 dm Offer Sustainability REACh Regulation REACh Peclaration REACh free of SVHC Yes EU RoHS Directive Compliant EU RoHS Declaration Toxic heavy metal free Yes Mercury free Yes RoHS exemption information Yes China RoHS Regulation China RoHS declaration	Package 1 Height	0.400 dm	
Offer Sustainability REACh Regulation REACh Declaration REACh free of SVHC Yes EU RoHS Directive Compliant EU RoHS Declaration Toxic heavy metal free Yes Mercury free Yes RoHS exemption information Yes China RoHS Regulation China RoHS declaration	Package 1 width	0.800 dm	
REACh Regulation REACh Declaration REACh free of SVHC Yes EU RoHS Directive Compliant EU RoHS Declaration Toxic heavy metal free Yes Mercury free Yes RoHS exemption information Yes China RoHS Regulation China RoHS declaration	Package 1 Length	1.050 dm	
REACh free of SVHC EU RoHS Directive Compliant EU RoHS Declaration Toxic heavy metal free Yes Mercury free Yes RoHS exemption information Yes China RoHS Regulation China RoHS declaration			
EU RoHS Directive Compliant EU RoHS Declaration Toxic heavy metal free Yes Mercury free Yes RoHS exemption information Yes China RoHS Regulation China RoHS declaration	<u> </u>		
EU RoHS Declaration Toxic heavy metal free Yes Mercury free Yes RoHS exemption information Yes China RoHS Regulation China RoHS declaration			
Mercury free Yes RoHS exemption information Yes China RoHS Regulation China RoHS declaration	EU RoHS Directive		
RoHS exemption information Yes China RoHS Regulation China RoHS declaration	Toxic heavy metal free	Yes	
China RoHS Regulation China RoHS declaration	Mercury free	Yes	
	RoHS exemption information	Yes	
	China RoHS Regulation		

WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	
Contractual warranty		
Warranty	18 months	