

TeSys D contactor - 3P(3 NO) - AC-3 - <= 440 V 12 A - 24 V DC coil

LC1D12BD

Main

Range of product	TeSys Deca	
Product or component type	Contactor	
Device short name	LC1D	
Contactor application	Resistive load Motor control	
Utilisation category	AC-1 AC-4 AC-3 AC-3e	
Poles description	3P	
[Ue] rated operational voltage	Power circuit: <= 690 V AC 25400 Hz Power circuit: <= 300 V DC	
[le] rated operational current	25 A (at <60 °C) at <= 440 V AC AC-1 for power circuit 12 A (at <60 °C) at <= 440 V AC AC-3 for power circuit 12 A (at <60 °C) at <= 440 V AC AC-3e for power circuit	
[Uc] control circuit voltage	24 V DC	

Complementary

Motor power kW	3 kW at 220230 V AC 50/60 Hz (AC-3)			
	5.5 kW at 380400 V AC 50/60 Hz (AC-3)			
	5.5 kW at 415440 V AC 50/60 Hz (AC-3)			
	7.5 kW at 500 V AC 50/60 Hz (AC-3)			
	7.5 kW at 660690 V AC 50/60 Hz (AC-3)			
	3.7 kW at 400 V AC 50/60 Hz (AC-4)			
	3 kW at 220230 V AC 50/60 Hz (AC-3e)			
	5.5 kW at 380400 V AC 50/60 Hz (AC-3e)			
	5.5 kW at 415440 V AC 50/60 Hz (AC-3e)			
	7.5 kW at 500 V AC 50/60 Hz (AC-3e)			
	7.5 kW at 660690 V AC 50/60 Hz (AC-3e)			
Motor power hp	0.5 hp at 115 V AC 50/60 Hz for 1 phase motors			
	2 hp at 230/240 V AC 50/60 Hz for 1 phase motors			
	3 hp at 200/208 V AC 50/60 Hz for 3 phases motors			
	3 hp at 230/240 V AC 50/60 Hz for 3 phases motors			
	7.5 hp at 460/480 V AC 50/60 Hz for 3 phases motors			
	10 hp at 575/600 V AC 50/60 Hz for 3 phases motors			
Compatibility code	LC1D			
Pole contact composition	3 NO			
Protective cover	With			
[Ith] conventional free air thermal	25 A (at 60 °C) for power circuit			
current	10 A (at 60 °C) for signalling circuit			
Irms rated making capacity	250 A at 440 V for power circuit conforming to IEC 60947			
	140 A AC for signalling circuit conforming to IEC 60947-5-1			
	250 A DC for signalling circuit conforming to IEC 60947-5-1			
Rated breaking capacity	250 A at 440 V for power circuit conforming to IEC 60947			

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

[lcw] rated short-time withstand	105 A 40 °C - 10 s for power circuit
current	210 A 40 °C - 1 s for power circuit
	30 A 40 °C - 10 min for power circuit
	61 A 40 °C - 1 min for power circuit
	100 A - 1 s for signalling circuit
	120 A - 500 ms for signalling circuit
	140 A - 100 ms for signalling circuit
Associated fuse rating	10 A gG for signalling circuit conforming to IEC 60947-5-1
	40 A gG at <= 690 V coordination type 1 for power circuit
	25 A gG at <= 690 V coordination type 2 for power circuit
Average impedance	2.5 mOhm - Ith 25 A 50 Hz for power circuit
Power dissipation per pole	0.36 W AC-3
	1.56 W AC-1
	0.36 W AC-3e
[Ui] rated insulation voltage	Power circuit: 690 V conforming to IEC 60947-4-1
[-1]g.	Power circuit: 600 V CSA certified
	Power circuit: 600 V UL certified
	Signalling circuit: 690 V conforming to IEC 60947-1
	Signalling circuit: 600 V CSA certified
	Signalling circuit: 600 V UL certified
	Signaling circuit. 600 v OE certified
Overvoltage category	III
pollution degree	3
[Uimp] rated impulse withstand voltage	6 kV conforming to IEC 60947
Safety reliability level	B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1
	B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO
	13849-1
Mechanical durability	30 Mcycles
Electrical durability	2 Mcycles 12 A AC-3 at Ue <= 440 V
	0.8 Mcycles 25 A AC-1 at Ue <= 440 V
	2 Mcycles 12 A AC-3e at Ue <= 440 V
Control circuit type	DC standard
Coil technology	With integral suppression device
Control circuit voltage limits	0.10.25 Uc (-4070 °C):drop-out DC
	0.71.25 Uc (-4070 °C):operational DC
	11.25 Uc (6070 °C):operational DC
	11.20 00 (0070 0).operational 00
Inrush power in W	5.4 W (at 20 °C)
Hold-in power consumption in W	5.4 W at 20 °C
Operating time	63 ±15 % ms closing
-	20 ±20 % ms opening
Time constant	20
	28 ms
Maximum operating rate	3600 cyc/h at 60 °C

Connections - terminals	Power circuit: screw clamp terminals 1 14 mm ² - cable stiffness: flexible without cable end	
	Power circuit: screw clamp terminals 2 14 mm ² - cable stiffness: flexible without cable end	
	Power circuit: screw clamp terminals 1 14 mm² - cable stiffness: flexible with cable	
	end Power circuit: screw clamp terminals 2 12.5 mm² - cable stiffness: flexible with	
	cable end Power circuit: screw clamp terminals 1 14 mm² - cable stiffness: solid without cable	
	end	
	Power circuit: screw clamp terminals 2 14 mm ² - cable stiffness: solid without cable end	
	Control circuit: screw clamp terminals 1 14 mm² - cable stiffness: flexible without cable end	
	Control circuit: screw clamp terminals 2 14 mm² - cable stiffness: flexible without cable end	
	Control circuit: screw clamp terminals 1 14 mm² - cable stiffness: flexible with cable	
	end Control circuit: screw clamp terminals 2 12.5 mm² - cable stiffness: flexible with	
	cable end Control circuit: screw clamp terminals 1 14 mm² - cable stiffness: solid without	
	cable end	
	Control circuit: screw clamp terminals 2 14 mm² - cable stiffness: solid without cable end	
Tightening torque	Power circuit: 1.7 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm	
	Power circuit: 1.7 N.m - on screw clamp terminals - with screwdriver Philips No 2 Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm	
	Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver hat 9 0 min	
	Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver pozidriv No 2 Power circuit: 1.7 N.m - on screw clamp terminals - with screwdriver pozidriv No 2	
Auxiliary contact composition	1 NO + 1 NC	
Auxiliary contacts type	type mechanically linked 1 NO + 1 NC conforming to IEC 60947-5-1	
,	type mirror contact 1 NC conforming to IEC 60947-3-1	
Signalling circuit frequency	25400 Hz	
Minimum switching voltage	17 V for signalling circuit	
Minimum switching current	5 mA for signalling circuit	
Insulation resistance	> 10 MOhm for signalling circuit	
Non-overlap time	1.5 ms on de-energisation between NC and NO contact 1.5 ms on energisation between NC and NO contact	
Mounting support	Plate Rail	
Environment		
Standards	CSA C22.2 No 14	
	EN 60947-4-1	
	EN 60947-5-1 IEC 60947-4-1	
	IEC 60947-5-1	
	UL 60947-4-1	
	IEC 60335-1:Clause 30.2	
	IEC 60335-2-40:Annex JJ UL 60335-2-40:Annex JJ	
	UL 60335-2-40:Annex JJ CSA C22.2 No 60947-4-1	
Product certifications	UL	
	CCC	
	CSA Marine	
	UKCA	
	EAC CB Scheme	
IP degree of protection	IP20 front face conforming to IEC 60529	
Protective treatment	TH conforming to IEC 60068-2-30	
Climatic withstand	conforming to IACS E10 exposure to damp heat	
oado widistalla	conforming to IACS E10 exposure to damp heat	

conforming to IEC 60947-1 Annex Q category D exposure to damp heat

Permissible ambient air temperature around the device	-4060 °C 6070 °C with derating	
Operating altitude	03000 m	
Fire resistance	850 °C conforming to IEC 60695-2-1	
Flame retardance	V1 conforming to UL 94	
Mechanical robustness	Vibrations contactor open (2 Gn, 5300 Hz) Vibrations contactor closed (4 Gn, 5300 Hz) Shocks contactor open (10 Gn for 11 ms) Shocks contactor closed (15 Gn for 11 ms)	
Height	77 mm	
Width	45 mm	
Depth	95 mm	
Net weight	0.485 kg	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.000 cm
Package 1 Width	9.000 cm
Package 1 Length	11.000 cm
Package 1 Weight	520.300 g
Unit Type of Package 2	S02
Number of Units in Package 2	15
Package 2 Height	15.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	8.078 kg
Unit Type of Package 3	P06
Number of Units in Package 3	240
Package 3 Height	75.000 cm
Package 3 Width	60.000 cm
Package 3 Length	80.000 cm
Package 3 Weight	136.620 kg

Contractual warranty

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

∇ Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	37
Environmental Disclosure	Product Environmental Profile

Use Better

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant with Exemptions
SCIP Number	50ae7612-fd2e-41e4-a369-50d0dea6e592
REACh Regulation	REACh Declaration
PVC free	Yes


Use Again

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	No

LC1D12BD

Dimensions Drawings

Dimensions




(1) Minimum electrical clearance

LC1		D09D18	D093D123	D099D129
b		77	99	80
	without cover or add-on blocks	93	93	93
С	with cover, without add-on blocks	95	95	95
с1	with LAD N or C (2 or 4 contacts)	126	126	126
c2	with LA6 DK10	138	138	138
23	with LAD T, R, S	146	146	146
с3	with LAD T, R, S and sealing cover	150	150	150

Connections and Schema

Wiring



Product datasheet

LC1D12BD

Image of product / Alternate images

Alternative







Product datasheet

LC1D12BD

Technical Illustration

Assembly's dimensions

