

long terminal shield - 3 poles - Compact NSX100..250

LV429517

Main

Product or component type	Long terminal shield
Range compatibility	ComPacT ComPacT NSX100
	ComPacT ComPacT NSX160
	ComPacT ComPacT NSX250
	ComPact ComPact NSX100
	ComPact ComPact NSX160
	ComPact ComPact NSX250
	ComPacT ComPacT NSX DC NSX100 DC
	ComPacT ComPacT NSX DC NSX160 DC
	ComPacT ComPacT NSX DC NSX250 DC
	ComPact Compact NSX100 DC
	ComPact Compact NSX160 DC
	ComPact Compact NSX250 DC
	EasyPact EasyPact CVS100
	EasyPact EasyPact CVS160
	EasyPact EasyPact CVS250
Accessory / separate part type	Insulation accessories
Poles description	3P
Quantity per set	1

Complementary

Connection pitch	35 mm	
IP degree of protection	IP40 conforming to IEC 60529	
Product compatibility	Circuit-breaker Plug-in base	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.000 cm
Package 1 Width	9.000 cm
Package 1 Length	13.000 cm
Package 1 Weight	151.300 g
Unit Type of Package 2	S04
Number of Units in Package 2	56
Package 2 Height	30.000 cm
Package 2 Width	40.000 cm
Package 2 Length	60.000 cm
Package 2 Weight	9.278 kg

Unit Type of Package 3	P12
Number of Units in Package 3	224
Package 3 Height	45.000 cm
Package 3 Width	80.000 cm
Package 3 Length	120.000 cm
Package 3 Weight	48.888 kg

Contractual warranty

Warranty 12 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

∅ Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	1
Environmental Disclosure	Product Environmental Profile

Use Better

Recycled metal content at CR level	0
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
REACh Regulation	REACh Declaration
Halogen content performance	Product contains halogen above thresholds
PVC free	Yes

Use Again

○ Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
Take-back	No